BDWOF-DSTRIM

DRAIN & TAILPIECE FOR USE WITH BDWOF-DSROUGH






Ø2 - 7/8"

SPECIFICATION SHEET

- FOR USE WITH BDWOF-DSROUGH ONLY
- FOR FREE-STANDING TUBS WITH INTEGRAL OVERFLOW
- INCLUDES EZ-CLICK™ TUB DRAIN, TAILPIECE, AND INSTALLATION TOOLS
- FITS MINIMUM TUB THICKNESS 1-1/4", MAXIMUM THICKNESS 2"
 - NOTE: FOR THINNER TUBS, USE ALTERNATIVE GASKET BDWOF-DS/SPACER (INCLUDED)
- FITS 2" DIAMETER DRAIN HOLE
- SIMPLIFIES INSTALLATION OF FREE-STANDING TUBS
- EZ-CLICK™ TUB DRAIN IS SNAKEABLE & FEATURES REMOVABLE HAIR CATCHER
- ALLOWS FOR DRAIN TO BE REMOVED WITHOUT REMOVING THE TUB

INSTALLATION TOOLS

BDWOF-DS/SPACER: OPTIONAL SPACER GASKET FOR TUBS LESS THAN 1 - 1/4" THICK—



7 - 11/16"

WARRANTY

FOR WARRANTY INFO PLEASE VISIT WWW.MOUNTAINPLUMBING.COM/WARRANTY-CLAIMS

FINISH CARE & MAINTENANCE

NEVER USE ANY HARSH ALKALI, ACID BASED DETERGENTS OR CLEANERS SUCH AS SOFT SCRUB®, SCRUBBING BUBBLES® OR COMET® TO CLEAN. DO NOT USE BRILLO® OR SCOTCH BRITE® PADS. THESE WILL ALL HARM THE FINISH. TO CLEAN, USE ONLY A DAMP SOFT CLOTH AND WIPE GENTLY. STANDARD WINDEX® CAN ALSO BE USED SPARINGLY. IT IS NOT NECESSARY TO WIPE HARD TO REMOVE SPOTS. TO MAINTAIN THE FINISH, WIPE WITH A SOFT DRY CLOTH AFTER USE. AN OCCASIONAL COAT OF PURE CARNAUBA WAX WITHOUT CLEANERS WILL HELP PORTECT THE FINISH.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE www.mountainplumbing.com 888-222-9140 fax 972-456-2719